

## Technical data sheet

Article number:  
156-01126

**T50RHDM8**

|                                     |                                                                                                                        |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>Product Group</b>                | 2-piece fixing ties for heavy duty applications, for screws                                                            |
| <b>Product Family</b>               | HDM8-Series for M8-Screws                                                                                              |
| <b>Material</b>                     | Polyamide 4.6 (PA46)                                                                                                   |
| <b>Colour</b>                       | Grey (GY)                                                                                                              |
| <b>Application Tool</b>             | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
| <b>Bundle Diameter max (metric)</b> | 50.0 mm                                                                                                                |
| <b>Bundle Ø min.</b>                | 15.0 mm                                                                                                                |
| <b>Cable Tie</b>                    | Polyamide 4.6 (PA46)                                                                                                   |
| <b>Fixation Method</b>              | Fixing hole                                                                                                            |
| <b>Flammability</b>                 | UL 94 V2                                                                                                               |
| <b>Foot Part</b>                    | Polyamide 4.6 (PA46)                                                                                                   |
| <b>for Hole Ø (FH)</b>              | 8.4 mm                                                                                                                 |
| <b>Height (H)</b>                   | 16.0 mm                                                                                                                |
| <b>Length (L)</b>                   | 200.0 mm                                                                                                               |
| <b>Length (L2)</b>                  | 37.5 mm                                                                                                                |
| <b>Min.Tensile Strength</b>         | 225 N                                                                                                                  |
| <b>Mounting Screw Type</b>          | M8 Screw                                                                                                               |
| <b>Operating Temperature</b>        | -40 °C to +150 °C                                                                                                      |
| <b>Package Content packed in</b>    | bag                                                                                                                    |
| <b>Pack Cont.</b>                   | 500 pcs.                                                                                                               |
| <b>ROHS compliant</b>               | Yes                                                                                                                    |
| <b>Stud Ø</b>                       | M8                                                                                                                     |
| <b>Thickness (T)</b>                | 1.2 mm                                                                                                                 |
| <b>Variant</b>                      | Inside Serrated                                                                                                        |
| <b>Width (W)</b>                    | 4.6 mm                                                                                                                 |

