

Technical data sheet

Article number: 156-01520

Product Group

T120ROSFT9HCLG



Product Family	Fir tree parts FT9
Material	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Bundle Ø max.	105.0 mm
Bundle Ø min.	5.0 mm
CE Certification	No
Fixation Method	Fir tree for round holes
Flammability	UL 94 HB
for Hole Ø (FH)	8.7 - 9.2 mm
Height (H)	29.2 mm
Length (L)	383.5 mm
Min.Tensile Strength	535 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	pack
Pack Cont.	500 pc.
Panel Thickness	15.8 mm
Panel Thickness max.	1.0 - 15.8 mm
Panel Thickness min. (metric)	1.0 mm
ROHS compliant	Yes
Thickness (T)	1.8 mm
Variant	Outside Serrated
Width (W)	7.6 mm
-	

2-piece fixing ties with fir tree, with disc, for round holes

RoHS