

## Technical data sheet

**Article number:**  
**156-01545**

**T30ROSEC0.5-2.5TV-SD**

|                                      |                                                                                                           |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------|
| <b>Product Group</b>                 | 2-piece fixing ties for edges                                                                             |
| <b>Product Family</b>                | EdgeClip-Series, 0.5 - 2.5 mm, top fixing                                                                 |
| <b>Material</b>                      | Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS) |
| <b>Colour</b>                        | Black (BK)                                                                                                |
| <b>Application Tool</b>              | MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7ISP                                             |
| <b>Bundle Ø max.</b>                 | 30 mm                                                                                                     |
| <b>Bundle Ø min.</b>                 | 1.5 mm                                                                                                    |
| <b>Cable Tie</b>                     | Polyamide 6.6, heat stabilised (PA66HS)                                                                   |
| <b>Fixation Method</b>               | EdgeClip, top, assembled, 2 piece                                                                         |
| <b>Foot Part</b>                     | Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)                                          |
| <b>Height (H)</b>                    | 1.2 mm                                                                                                    |
| <b>Length (L)</b>                    | 145.0 mm                                                                                                  |
| <b>Length (L2)</b>                   | 13.0 mm                                                                                                   |
| <b>Min.Tensile Strength</b>          | 133 N                                                                                                     |
| <b>Operating Temperature</b>         | -40 °C to +105 °C                                                                                         |
| <b>Package Content packed in</b>     | bag                                                                                                       |
| <b>Pack Cont.</b>                    | 500 pcs.                                                                                                  |
| <b>Panel Thickness</b>               | 2.5 mm                                                                                                    |
| <b>Panel Thickness min. (metric)</b> | 0.5 mm                                                                                                    |
| <b>ROHS compliant</b>                | Yes                                                                                                       |
| <b>Thickness (T)</b>                 | 1.2 mm                                                                                                    |
| <b>Variant</b>                       | Outside Serrated                                                                                          |
| <b>Width (W)</b>                     | 3.4 mm                                                                                                    |

