


Technical data sheet

Article number: 156-01711

Product Group

T50RSRAH6.5SD



Product Group	z-piece fixing ties with arrownead, with disc
Product Family	for round holes, sealed
Material	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV), Thermoplastic Elastomer (TPE)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	50.0 mm
Bundle Ø min.	3.0 mm
Cable Tie	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)
CE Certification	No
Fixation Method	arrowhead
Foot Part	Thermoplastic Elastomer (TPE)
for Hole Ø (FH)	6.35 mm (hexagonal), 6.5 mm
Height (H)	13.25 mm
Length (L)	200 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	bag
Pack Cont.	4000 pcs.
Panel Thickness	1.1 mm
Panel Thickness max.	0.6 - 1.1 mm
Panel Thickness min. (metric)	0.6 mm
ROHS compliant	Yes
Width (W)	4.6 mm

2-piece fixing ties with arrowhead, with disc

