

## Technical data sheet

**Article number:**  
**156-01747**

**T50SOSSB5**

|                                  |   |
|----------------------------------|---|
| <b>Product Group</b>             | 2-Piece Fixing Ties for Weld , moveable                       |
| <b>Product Family</b>            | SB5 Series  |
| <b>Material</b>                  | Polyamide 6.6, heat stabilised (PA66HS), Polyacetal (POM)     |
| <b>Colour</b>                    | Black (BK)  |
| <b>Application Tool</b>          | MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7ISP |
| <b>Bundle Ø max.</b>             | 35.0 mm   |
| <b>Bundle Ø min.</b>             | 2.0 mm  |
| <b>Cable Tie</b>                 | Polyamide 6.6, heat stabilised (PA66HS)                       |
| <b>Fixation Method</b>           | Weld Stud Fixing  |
| <b>Flammability</b>              | UL 94 V2, UL 94 HB  |
| <b>Foot Part</b>                 | Polyacetal (POM)  |
| <b>Height (H)</b>                | 1.3 mm  |
| <b>Length (L)</b>                | 150 mm  |
| <b>Length (L2)</b>               | 20 mm   |
| <b>Min.Tensile Strength</b>      | 225 N   |
| <b>Operating Temperature</b>     | -40 °C to +105 °C   |
| <b>Package Content packed in</b> | bag   |
| <b>Pack Cont.</b>                | 250 pcs.  |
| <b>ROHS compliant</b>            | Yes   |
| <b>Stud Ø</b>                    | 5.0 mm  |
| <b>Variant</b>                   | Outside Serrated  |
| <b>Width (W)</b>                 | 4.6 mm  |

