


## **Technical data sheet**

Article number: 156-01756

**Product Group** 

**T80LFT6** 



Product Family	Fir tree parts FT6
Material	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO7, EVO7SP, EVO7iSP, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Bundle Ø max.	108.0 mm
Bundle Ø min.	5.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
Fixation Method	Fir Tree
Flammability	UL 94 HB
Foot Part	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
for Hole Ø (FH)	6.4 - 7.1 mm
Height (H)	1.3 mm
Length (L)	390 mm
Length (L2)	11.6 mm
Min.Tensile Strength	355 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	bag
Pack Cont.	500 pcs.
Panel Thickness	3.00 mm
Panel Thickness min. (metric)	0.75 mm
ROHS compliant	Yes
Variant	Inside Serrated
Width (W)	5.0 mm

2-piece fixing ties with fir tree, with disc, for round holes

**RoHS**