

## Technical data sheet

Article number:  
156-02247

**T50SVCMO C22M**

|                                  |                                                                           |
|----------------------------------|---------------------------------------------------------------------------|
| <b>Product Group</b>             | 2-piece fixing ties with pipe clip                                        |
| <b>Material</b>                  | Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV) |
| <b>Colour</b>                    | Black (BK)                                                                |
| <b>Bundle Ø max.</b>             | 25.0 mm                                                                   |
| <b>Bundle Ø min.</b>             | 20.0 mm                                                                   |
| <b>CE Certification</b>          | No                                                                        |
| <b>Fixation Method</b>           | Omega Clip                                                                |
| <b>Flammability</b>              | UL 94 HB                                                                  |
| <b>Height (H)</b>                | 48.5 mm                                                                   |
| <b>Length (L)</b>                | 36.5 mm                                                                   |
| <b>Length (L2)</b>               | 22.9 mm                                                                   |
| <b>Min.Tensile Strength</b>      | 225 N                                                                     |
| <b>Operating Temperature</b>     | -40 °C to +105 °C                                                         |
| <b>Package Content packed in</b> | pack                                                                      |
| <b>Pack Cont.</b>                | 1000 pcs.                                                                 |
| <b>ROHS compliant</b>            | Yes                                                                       |

HF ✓

RoHS ✓