

## Technical data sheet

**Article number:**  
**156-02482**

**T120RCPM8-TSSET**

<b>Material</b>	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
<b>Colour</b>	Black (BK)
<b>Bundle Ø max.</b>	105.0 mm
<b>Bundle Ø min.</b>	5.0 mm
<b>Cable Tie</b>	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
<b>CE Certification</b>	No
<b>Fixation Method</b>	Screw Mount
<b>Flammability</b>	UL 94 HB
<b>for Hole Ø (FH)</b>	8.4 mm
<b>Height (H)</b>	23.5 mm
<b>Length (L)</b>	385.0 mm
<b>Min.Tensile Strength</b>	535 N
<b>Mounting Screw Type</b>	M8 Screw
<b>Operating Temperature</b>	-40 °C to +110 °C
<b>Package Content packed in</b>	pack
<b>Pack Cont.</b>	1000 pcs.
<b>ROHS compliant</b>	Yes
<b>Stud Ø</b>	8.0 mm
<b>Thickness (T)</b>	1.8 mm
<b>Variant</b>	Inside Serrated
<b>Width (W)</b>	7.6 mm

