

## Technical data sheet

**Article number:**  
**156-02500**

**T50RFT11SET**

<b>Material</b>	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
<b>Colour</b>	Black (BK)
<b>Application Tool</b>	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
<b>Bundle Diameter max (metric)</b>	45.0 mm
<b>Fixation Method</b>	Fir Tree
<b>for Hole Ø (FH)</b>	10.8 - 11.2 mm
<b>Length (L)</b>	200.0 mm
<b>Min.Tensile Strength</b>	225 N
<b>Operating Temperature</b>	-40 °C to +105 °C
<b>Package Content packed in</b>	bag
<b>Pack Cont.</b>	1000 pcs.
<b>Panel Thickness max.</b>	1.0-10.0 mm
<b>ROHS compliant</b>	Yes
<b>Thickness (T)</b>	1.2 mm
<b>Variant</b>	Inside Serrated
<b>Width (W)</b>	4.6 mm

