

## Technical data sheet

Article number:  
156-02517

**T50RFT6ASET**

<b>Material</b>	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)
<b>Colour</b>	Black (BK)
<b>Bundle Ø max.</b>	50.0 mm
<b>Bundle Ø min.</b>	2.0 mm
<b>Cable Tie</b>	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)
<b>CE Certification</b>	No
<b>Fixation Method</b>	Fir tree for round holes
<b>for Hole Ø (FH)</b>	6.1 - 7.1 mm
<b>Height (H)</b>	16.4 mm
<b>Length (L)</b>	203.2 mm
<b>Min.Tensile Strength</b>	225 N
<b>Operating Temperature</b>	-40 °C to +105 °C
<b>Package Content packed in</b>	pack
<b>Pack Cont.</b>	5000 pcs.
<b>Panel Thickness</b>	3.5 mm
<b>Panel Thickness max.</b>	0.6 - 3.5 mm
<b>Panel Thickness min. (metric)</b>	0.6 mm
<b>ROHS compliant</b>	Yes
<b>Variant</b>	Inside Serrated
<b>Width (W)</b>	16.0 mm

