## HellermannTyton

## **Technical data sheet**

Article number: 156-02547

T120RFT11

	L
4	•

Product Group	2-piece fixing ties with fir tree, with disc, for round holes
Product Family	Fir tree parts FT11
Material	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Bundle Diameter max (metric)	105.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
Fixation Method	Fir Tree
Foot Part	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
for Hole Ø (FH)	10.8 - 11.2 mm
Length (L)	387.0 mm
Min.Tensile Strength	535 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	bag
Pack Cont.	100 pcs.
Panel Thickness	10.0 mm
Panel Thickness max.	1.0-10.0 mm
Panel Thickness min. (metric)	1.0 mm
ROHS compliant	Yes
Thickness (T)	1.9 mm
Variant	Inside Serrated
Width (W)	7.6 mm

RoHS

Technical changes and errors reserved. It's up to the customer to check the suitability for a specific application by means of tests.