

## Technical data sheet

Article number:  
156-04036

**WSIDFTM10WSSDSET**

|                                      |                                                                                                                                             |
|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Material</b>                      | Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS), Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV) |
| <b>Colour</b>                        | Orange (OG), High Voltage (HV), Black (BK)                                                                                                  |
| <b>Bundle Ø max.</b>                 | 82.6 mm                                                                                                                                     |
| <b>Bundle Ø min.</b>                 | 9.4 mm                                                                                                                                      |
| <b>CE Certification</b>              | No                                                                                                                                          |
| <b>Fixation Method</b>               | Fir tree for round holes                                                                                                                    |
| <b>Flammability</b>                  | UL 94 HB                                                                                                                                    |
| <b>for Hole Ø (FH)</b>               | 7.6 - 8.4 mm, M10 Threaded                                                                                                                  |
| <b>Height (H)</b>                    | 23.7 mm                                                                                                                                     |
| <b>Length (L)</b>                    | 307.0 mm                                                                                                                                    |
| <b>Min.Tensile Strength</b>          | 533 N                                                                                                                                       |
| <b>Operating Temperature</b>         | -40 °C to +105 °C                                                                                                                           |
| <b>Package Content packed in</b>     | carton                                                                                                                                      |
| <b>Pack Cont.</b>                    | 1200 pcs.                                                                                                                                   |
| <b>Panel Thickness</b>               | 6.0 mm                                                                                                                                      |
| <b>Panel Thickness max.</b>          | 0.6 - 6.0 mm                                                                                                                                |
| <b>Panel Thickness min. (metric)</b> | 0.6 mm                                                                                                                                      |
| <b>ROHS compliant</b>                | Yes                                                                                                                                         |
| <b>Variant</b>                       | Inside Serrated                                                                                                                             |
| <b>Width (W)</b>                     | 22.6 mm                                                                                                                                     |

