

Technical data sheet

Article number:
156-04037

WSIFT9HCLG



Product Group	2-piece fixing ties with fir tree, with disc, for round holes
Product Family	Fir tree parts FT9
Material	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS), Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)
Colour	Orange (OG), High Voltage (HV), Black (BK)
Application Tool	ProCut 9 no battery, MK9P, MK9P w/ Upper air, MK21, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9HT, EVO9i, EVO9iHT
Bundle Diameter max (metric)	82.6 mm
Bundle Ø min.	9.4 mm
CE Certification	No
Fixation Method	Fir Tree
Flammability	UL 94 HB
for Hole Ø (FH)	8.75 - 9.25 mm
Height (H)	1.4 mm
Length (L)	307.0 mm
Min.Tensile Strength	533 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	bag
Pack Cont.	100 pcs.
Panel Thickness	12.7 mm
Panel Thickness max.	1.0 - 12.7 mm
Panel Thickness min. (metric)	1.0 mm
ROHS compliant	Yes
Width (W)	13.97 mm

