

Technical data sheet

Article number:
156-04065

T50RX2DUALSDFT6.5A



Product Group	2-piece fixing ties with fir tree, with disc, for round holes
Product Family	Fir tree parts FT6
Material	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS), Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)
Colour	Orange (OG), High Voltage (HV), Black (BK)
Bundle Ø max.	50.0 mm
Bundle Ø min.	1.5 mm
Cable Tie	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
CE Certification	No
Fixation Method	Fir tree for round holes
Flammability	UL 94 HB
for Hole Ø (FH)	6.1 - 7.0 mm
Height (H)	20.5 mm
Length (L)	203.2 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	pack
Pack Cont.	500 pcs.
Panel Thickness	6.0 mm
Panel Thickness max.	0.6 - 6.0 mm
Panel Thickness min. (metric)	0.6 mm
ROHS compliant	Yes
Thickness (T)	1.2 mm
Width (W)	11.7 mm

