

Technical data sheet

Article number:
156-04066

T50RX2DUALSDSeal6.5A



Product Group	2-piece fixing ties with fir tree, with disc, for round holes
Product Family	Fir tree parts FT6
Material	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS), Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV), Thermoplastic Elastomer (TPE)
Colour	Orange (OG), High Voltage (HV), Black (BK)
Bundle Ø max.	50.0 mm
Bundle Ø min.	1.5 mm
Cable Tie	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
CE Certification	No
Fixation Method	Fir Tree
Flammability	UL 94 HB
for Hole Ø (FH)	6.1 - 6.9 mm
Height (H)	16.24 mm
Length (L)	46 mm
Operating Temperature	-40 °C to +110 °C
Package Content packed in	carton
Pack Cont.	1000 pcs.
Panel Thickness	1.1 mm
Panel Thickness max.	0.60 - 1.1 mm
Panel Thickness min. (metric)	0.60 mm
ROHS compliant	Yes
Width (W)	28.48 mm

HF ✓

RoHS ✓