

## Technical data sheet

Article number:  
156-04084

**T30RLPCPCM6TSSET**

|                                     |  |
|-------------------------------------|--|
| <b>Material</b>                     | Polyamide 6 (PA6), Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV) |
| <b>Colour</b>                       | Black (BK)   |
| <b>Bundle Diameter max (metric)</b> | 35.0 mm  |
| <b>Bundle Ø min.</b>                | 1.5 mm   |
| <b>Cable Tie</b>                    | Polyamide 6.6, high impact modified, heat and UV-resistant (PA66HIRHSW)                      |
| <b>CE Certification</b>             | No   |
| <b>Fixation Method</b>              | Screw Mount  |
| <b>Flammability</b>                 | UL 94 HB   |
| <b>Height (H)</b>                   | 8.5 mm   |
| <b>Length (L)</b>                   | 152.4 mm   |
| <b>Min.Tensile Strength</b>         | 135 N  |
| <b>Mounting Screw Type</b>          | #1/4" (M6) Screw   |
| <b>Operating Temperature</b>        | -40 °C to +105 °C  |
| <b>Package Content packed in</b>    | carton   |
| <b>Pack Cont.</b>                   | 2000 pcs.  |
| <b>ROHS compliant</b>               | Yes  |
| <b>Stud Ø</b>                       | 6.0 mm   |
| <b>Thickness (T)</b>                | 8.5 mm   |
| <b>Variant</b>                      | Inside Serrated  |
| <b>Width (W)</b>                    | 20.0 mm  |

