


Technical data sheet

Article number: 156-05902

Product Group

T50ROSFT6SD



1 Todact Group	2 Freee Fixing hes with the ree, with bise, for Round Froies
Product Family	Fir tree parts FT6
Material	Polyamide 6.6, heat stabilised (PA66HS), Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	46.0 mm
Bundle Ø min.	1.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
Fixation Method	Fir Tree
Flammability	UL 94 HB
Foot Part	Polyamide 6.6, high impact modified (PA66HIR)
for Hole Ø (FH)	6.4 - 7.1 mm
Height (H)	1.3 mm
Length (L)	200.0 mm
Length (L2)	11.6 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	pcs.
Pack Cont.	500 pcs.
Panel Thickness	3.0 mm
Panel Thickness min. (metric)	0.75 mm
ROHS compliant	Yes
Variant	Outside Serrated
Width (W)	4.6 mm

2-Piece Fixing Ties with Fir Tree, with Disc, for Round Holes

RoHS