


Technical data sheet

Article number: 157-00016

T50SOS3DOP65X130-E



Product Group	1-Piece Fixing Ties with Fir Tree, with Disc, for Oval Holes
Product Family	for oval holes
Material	Polyamide 6.6, heat stabilised (PA66HS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP, FTS_pro
Bundle Ø max.	35.0 mm
Bundle Ø min.	1.5 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
Fixation Method	Fir Tree for oval holes
Flammability	UL 94 V2

CUDIC TIC	r oryannae o.o, neat stabilisea (17.00113)
Fixation Method	Fir Tree for oval holes
Flammability	UL 94 V2
for Hole Ø (FH)	6.5 x 13.0 mm
Height (H)	1.3 mm
Length (L)	165.0 mm
Min.Tensile Strength	180 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	bag
Pack Cont.	1500 pcs.
Panel Thickness	5.0 mm
Panel Thickness max.	0.7 – 5.0 mm
Panel Thickness min. (metric)	0.7 mm
ROHS compliant	Yes
Thickness (T)	1.3 mm
Variant	Outside Serrated
Width (W)	4.6 mm

