

Technical data sheet

Article number:
157-00050

T50SOSFT6LGU



Product Group	1-piece fixing ties with fir tree, with disc, for round holes
Product Family	Fir tree parts FT6
Material	Polyamide 6.6, heat stabilised (PA66HS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO7, EVO7SP, EVO7iSP, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Bundle Ø max.	35.0 mm
Bundle Ø min.	1.0 mm
CE Certification	No
Fixation Method	Fir tree for round holes
Flammability	UL 94 V2
for Hole Ø (FH)	6.5 - 7.2 mm
Height (H)	1.5 mm
Length (L)	169.0 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +125 °C
Package Content packed in	pack
Pack Cont.	500 pcs.
Panel Thickness	8.5 mm
Panel Thickness max.	0.6 - 8.5 mm
Panel Thickness min. (metric)	0.6 mm
ROHS compliant	Yes
Thickness (T)	1.5 mm
Variant	Outside Serrated
Width (W)	5.1 mm

