

## Technical data sheet

Article number:  
157-00053

T50SOSFT7X12U



<b>Product Group</b>	1-piece fixing ties with fir tree, with disc
<b>Product Family</b>	for oval holes
<b>Material</b>	Polyamide 6.6, heat stabilised (PA66HS)
<b>Colour</b>	Black (BK)
<b>Application Tool</b>	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO7, EVO7SP, EVO7iSP, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
<b>Bundle Ø max.</b>	35.0 mm
<b>Bundle Ø min.</b>	1.0 mm
<b>Cable Tie</b>	Polyamide 6.6, heat stabilised (PA66HS)
<b>CE Certification</b>	No
<b>Fixation Method</b>	Fir tree for round holes
<b>Flammability</b>	UL 94 V2
<b>for Hole Ø (FH)</b>	7.0 x 12.0 mm
<b>Height (H)</b>	11.3 mm
<b>Length (L)</b>	165.0 mm
<b>Min.Tensile Strength</b>	225 N
<b>Operating Temperature</b>	-40 °C to +125 °C
<b>Package Content packed in</b>	pack
<b>Pack Cont.</b>	500 pcs.
<b>Panel Thickness</b>	4.0 mm
<b>Panel Thickness max.</b>	0.6 - 4.0 mm
<b>Panel Thickness min. (metric)</b>	0.6 mm
<b>ROHS compliant</b>	Yes
<b>Thickness (T)</b>	1.52 mm
<b>Variant</b>	Outside Serrated
<b>Width (W)</b>	5.08 mm

