

## **Technical data sheet**


Article number: 157-00054

**Product Group** 

Thickness (T)
Variant

Width (W)

T50ROSFT7X12U



•	J
Product Family	for oval holes
Material	Polyamide 6.6, heat stabilised (PA66HS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO7, EVO7SP, EVO7iSP, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Bundle Ø max.	50.0 mm
Bundle Ø min.	2.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
CE Certification	No
Fixation Method	Fir tree for round holes
Flammability	UL 94 V2
for Hole Ø (FH)	7.0 x 12.0 mm
Height (H)	10.5 mm
Length (L)	215.9 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +125 °C
Package Content packed in	pack
Pack Cont.	500 pcs.
Panel Thickness	4.0 mm
Panel Thickness max.	0.6 - 4.0 mm
Panel Thickness min. (metric)	0.6 mm
ROHS compliant	Yes
Panel Thickness min. (metric)	0.6 mm

1-piece fixing ties with fir tree, with disc

RoHS

Outside Serrated

1.5 mm

5.08 mm