

Technical data sheet

Article number:
157-00131

T50ROSFTM6SO12.5B

Product Group	1-piece fixing ties with fir tree, with disc, with stand-off, for round holes
Product Family	With offset 12.5 and 25.0 mm
Material	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	50.0 mm
Bundle Ø min.	2.0 mm
CE Certification	No
Fixation Method	Fir tree for round holes
for Hole Ø (FH)	M6
Height (H)	21.40 mm
Length (L)	215.9 mm
Length (L2)	12.5 mm
Min.Tensile Strength	222.4 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	pack
Pack Cont.	500 pcs.
Panel Thickness	6.65 mm
Panel Thickness max.	0.6 - 6.65 mm
Panel Thickness min. (metric)	0.6 mm
ROHS compliant	Yes
Width (W)	4.6 mm

