


Technical data sheet

Article number: 157-00183

T50SOS2DOP62x122-E



| 1-piece fixing ties with fir tree, with disc |
|--|
| for oval holes |
| Polyamide 6.6, heat stabilised (PA66HS) |
| Black (BK) |
| |
| |

| Application Tool | MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP, FTS_pro |
|-------------------------------|--|
| Bundle Ø max. | 35.0 mm |
| Bundle Ø min. | 1.0 mm |
| Cable Tie | Polyamide 6.6, heat stabilised (PA66HS) |
| Fixation Method | Fir tree for round holes |
| Flammability | UL 94 V2 |
| for Hole Ø (FH) | 6.2 x 12.2 mm |
| Height (H) | 10.5 mm |
| Length (L) | 164.0 mm |
| Min.Tensile Strength | 225 N |
| Operating Temperature | -40 °C to +105 °C |
| Package Content packed in | bag |
| Pack Cont. | 500 pcs. |
| Panel Thickness | 6.0 mm |
| Panel Thickness max. | 0.6 - 6.0 mm |
| Panel Thickness min. (metric) | 0.6 mm |
| ROHS compliant | Yes |
| Thickness (T) | 1.3 mm |
| Variant | Outside Serrated |
| Width (W) | 4.6 mm |

