

## Technical data sheet

**Article number:**  
**157-00196**

**T50ROSFT825SO**

<b>Product Group</b>	1-piece fixing ties with fir tree, with disc, with stand-off, for round holes
<b>Product Family</b>	With offset 12.5 and 25.0 mm
<b>Material</b>	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)
<b>Colour</b>	Black (BK)
<b>Application Tool</b>	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO7, EVO7SP, EVO7iSP, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
<b>Bundle Ø max.</b>	50.0 mm
<b>Bundle Ø min.</b>	2.0 mm
<b>CE Certification</b>	No
<b>Fixation Method</b>	Fir tree for round holes
<b>for Hole Ø (FH)</b>	7.6 - 8.4 mm
<b>Length (L)</b>	245.1 mm
<b>Length (L2)</b>	25.0 mm
<b>Min.Tensile Strength</b>	225 N
<b>Operating Temperature</b>	-40 °C to +105 °C
<b>Package Content packed in</b>	pack
<b>Pack Cont.</b>	500 pcs.
<b>Panel Thickness</b>	6.0 mm
<b>Panel Thickness max.</b>	0.6 - 6.0 mm
<b>Panel Thickness min. (metric)</b>	0.6 mm
<b>ROHS compliant</b>	Yes
<b>Width (W)</b>	5.1 mm

