

Technical data sheet

Article number:
157-00225

T50ROSFTOVAL12.5A

| | |
|--------------------------------------|--|
| Product Group | 1-piece fixing ties with fir tree, with disc, with stand-off, for oval holes |
| Product Family | with offset 12.5 and 25.0 mm |
| Material | Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS) |
| Colour | Grey (GY) |
| Application Tool | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
| Bundle Ø max. | 50.0 mm |
| Bundle Ø min. | 2.0 mm |
| CE Certification | No |
| Fixation Method | Fir Tree for oval holes |
| Flammability | UL 94 HB |
| for Hole Ø (FH) | 6.2 x 12.2 mm, 6.5 x 12.5 mm, 6.5 x 13.0 mm, 7.0 x 12.0 mm |
| Height (H) | 13.15 mm |
| Length (L) | 215.9 mm |
| Length (L2) | 12.5 mm |
| Min.Tensile Strength | 225 N |
| Operating Temperature | -40 °C to +105 °C |
| Package Content packed in | pack |
| Pack Cont. | 500 pcs. |
| Panel Thickness | 6.75 mm |
| Panel Thickness max. | 0.6 - 6.75 mm |
| Panel Thickness min. (metric) | 0.6 mm |
| ROHS compliant | Yes |
| Thickness (T) | 1.35 mm |
| Variant | Outside Serrated |
| Width (W) | 4.70 mm |

