

Technical data sheet

Article number:
157-00370

T50SOSFTOVALU



Product Group	1-piece fixing ties with fir tree, with disc
Product Family	for oval holes
Material	Polyamide 6.6, heat stabilised (PA66HS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Bundle Ø max.	35.0 mm
Bundle Ø min.	2.0 mm
Cable Tie	Polyamide 6.6, heat stabilised (PA66HS)
CE Certification	No
Fixation Method	Fir Tree for oval holes
Flammability	UL 94 V2
for Hole Ø (FH)	6.2 x 12.2 mm, 6.5 x 12.5 mm, 6.5 x 13.0 mm, 7.0 x 12.0 mm
Height (H)	12.85 mm
Length (L)	168.2 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +125 °C
Package Content packed in	pack
Pack Cont.	1000 pcs.
Panel Thickness	6.75 mm
Panel Thickness max.	0.6 - 6.75 mm
Panel Thickness min. (metric)	0.6 mm
ROHS compliant	Yes
Variant	Outside Serrated
Width (W)	5.1 mm

