

Technical data sheet

Article number:
157-00421

T50ROSFT5.6SO25R

Product Group	1-piece fixing ties with fir tree, with disc, with stand-off, for round holes
Product Family	With offset 12.5 and 25.0 mm
Material	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO7, EVO7SP, EVO7iSP, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Bundle Ø max.	50.0 mm
Bundle Ø min.	2.0 mm
CE Certification	No
Fixation Method	Fir tree for round holes
Flammability	UL 94 HB
for Hole Ø (FH)	5.4 - 5.8 mm
Height (H)	19.25 mm
Length (L)	239.0 mm
Length (L2)	25.0 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	pack
Pack Cont.	1000 pcs.
Panel Thickness	4.25 mm
Panel Thickness max.	3.0 - 4.25 mm
Panel Thickness min. (metric)	3.0 mm
ROHS compliant	Yes
UL-File Number	E64139
Variant	Outside Serrated
Width (W)	5.08 mm

