

Technical data sheet

Article number:
157-00519

T50ROSFT612.5SO

Product Group	1-piece fixing ties with fir tree, with disc, with stand-off, for round holes
Product Family	With offset 12.5 and 25.0 mm
Material	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO7, EVO7SP, EVO7iSP, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Bundle Ø max.	50.0 mm
Bundle Ø min.	2.0 mm
Cable Tie	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
CE Certification	No
Fixation Method	Fir tree for round holes
Flammability	UL 94 HB
for Hole Ø (FH)	6.1 - 6.9 mm
Height (H)	16.1 mm
Length (L)	234.2 mm
Length (L2)	12.5 mm
Min.Tensile Strength	222.4 N
Operating Temperature	-40 °C to +105 °C
Package Content packed in	carton
Pack Cont.	3000 pcs.
Panel Thickness	6.0 mm
Panel Thickness max.	0.6 - 6.0 mm
Panel Thickness min. (metric)	0.6 mm
ROHS compliant	Yes
Thickness (T)	1.5 mm
Width (W)	5.1 mm

