HellermannTyton

Technical data sheet

Article number: 167-00531

FG17-M20



Product FamilyFG straight fitting with swivel thread, IP54MaterialPolypropylene (PP)ColourGrey (GY)A/F Thread (A/F2)24 mmDiameter (D)26.4 mmFlammabilityUL 94 V2Halogen-freeYesLength (L)45.0 mmNominal Ø17 mmOperating Temperature-35 °C to +80 °C	Product Group	Fittings for FlexiGuard spiral-reinforced PVC Conduits
Material Polypropylene (PP) Colour Grey (GY) A/F Thread (A/F2) 24 mm Diameter (D) 26.4 mm Flammability UL 94 V2 Halogen-free Yes Length (L) 45.0 mm Nominal Ø 17 mm Operating Temperature -35 °C to +80 °C	•	
ColourGrey (GY)A/F Thread (A/F2)24 mmDiameter (D)26.4 mmFlammabilityUL 94 V2Halogen-freeYesLength (L)45.0 mmNominal Ø17 mmOperating Temperature-35 °C to +80 °C	•	
Diameter (D) 26.4 mm Flammability UL 94 V2 Halogen-free Yes Length (L) 45.0 mm Nominal Ø 17 mm Operating Temperature -35 °C to +80 °C	Colour	
Diameter (D) 26.4 mm Flammability UL 94 V2 Halogen-free Yes Length (L) 45.0 mm Nominal Ø 17 mm Operating Temperature -35 °C to +80 °C		
FlammabilityUL 94 V2Halogen-freeYesLength (L)45.0 mmNominal Ø17 mmOperating Temperature-35 °C to +80 °C	A/F Thread (A/F2)	24 mm
Halogen-freeYesLength (L)45.0 mmNominal Ø17 mmOperating Temperature-35 °C to +80 °C	Diameter (D)	26.4 mm
Length (L) 45.0 mm Nominal Ø 17 mm Operating Temperature -35 °C to +80 °C	Flammability	UL 94 V2
Nominal Ø 17 mm Operating Temperature -35 °C to +80 °C	Halogen-free	Yes
Operating Temperature -35 °C to +80 °C	Length (L)	45.0 mm
	Nominal Ø	17 mm
Outside Ø (OD) 26.4 mm	Operating Temperature	-35 °C to +80 °C
	Outside Ø (OD)	26.4 mm
Pack Cont. 10 pcs.	Pack Cont.	10 pcs.
Package Content packed in bag	Package Content packed in	bag



Technical changes and errors reserved. It's up to the customer to check the suitability for a specific application by means of tests.