

## Technical data sheet

Article number:  
300-06010

TU28-50.8/25.4



<b>Product Group</b>	Heat shrinkable tubing 2:1 - self-extinguishing, halogen-free and diesel resistant
<b>Product Family</b>	TU28 - thin-walled
<b>Material</b>	Polyolefin, cross-linked (PO-X)
<b>Colour</b>	Black (BK)
<b>Behaviour at Heat Shock</b>	not fluid, not dripping, not cracking
<b>Dielectric Strength</b>	19.7 kV/mm
<b>Elongation at break</b>	200%
<b>Heat Shock Test</b>	4h/225°C
<b>Longitudinal Change After Shrinkage</b>	+/-5%
<b>Min. Shrink Temperature - °C</b>	+120 °C
<b>Operating Temperature</b>	-55 °C to +125 °C
<b>Package Content packed in</b>	reel
<b>Pack Cont.</b>	50 m
<b>Recov. Ø d max.</b>	25.40 mm
<b>Shrink Ratio</b>	2:1
<b>Specifications</b>	DIN EN 50343:2014 Appendix H, EN 45545-2
<b>Supplied Ø D min.</b>	53.0 mm
<b>Tensile Strength</b>	10.3 MPa
<b>Wall (WT)</b>	0.64 mm

HF ✓

RoHS ✓

EN 45545-2

EN 50343