


## Technical data sheet

Article number:  
300-30644

HIS-PACK-6.4/3.2



|                                     |                                       |
|-------------------------------------|---------------------------------------|
| Product Group                       | Heat shrinkable tubing 2:1 on a reel  |
| Product Family                      | HIS-PACK                              |
| Material                            | Polyolefin, cross-linked (PO-X)       |
| Colour                              | Grey (GY)                             |
| Behaviour at Heat Shock             | not dripping                          |
| Dielectric Strength [Test method]   | 20 kV/mm [IEC 243]                    |
| Elongation at break                 | 800% (IEC 684 P2)                     |
| Flammability                        | UL 224 VW-1                           |
| Heat Aging Test                     | 168h/175°C                            |
| Heat Shock Test                     | 4h/250°C                              |
| Insulation Class                    | E (VDE 0530)                          |
| Longitudinal Change After Shrinkage | +/-5%                                 |
| Min. Shrink Temperature - °C        | +100 °C                               |
| Operating Temperature               | -55 °C to +125 °C                     |
| Package Content packed in           | box                                   |
| Pack Cont.                          | 5 m                                   |
| Recov. Ø d max.                     | 3.2 mm                                |
| Shrink Ratio                        | 2:1                                   |
| Specifications                      | csa-C22.1, csa-C22.2 No.198.1, UL 224 |
| Supplied Ø D min.                   | 6.4 mm                                |
| Tensile Strength                    | 17 MPa                                |
| UL-File Number                      | E143529                               |
| Wall (WT)                           | 0.60 mm                               |
| Water Absorption                    | 0.15 %                                |

