

## Technical data sheet

Article number:  
300-70128

TCN30-12.0/4.0-BU



<b>Product Group</b>	Heat shrink tubing 3:1, thin-wall
<b>Product Family</b>	TCN30, self-extinguishing, in 1 m long
<b>Material</b>	Polyolefin, cross-linked (PO-X)
<b>Colour</b>	Blue (BU)
<b>Dielectric Strength [Test method]</b>	20 kV/mm [IEC 243]
<b>Elongation at break</b>	>400%
<b>Elongation At Heat Aging</b>	350 %
<b>Flammability</b>	UL 224 VW-1
<b>Heat Aging Test</b>	168h/160°C
<b>Longitudinal Change After Shrinkage</b>	-15% max.
<b>Min. Shrink Temperature - °C</b>	+100 °C
<b>Minimum Tensile Strength At Heat Aging</b>	14 MPa
<b>Operating Temperature</b>	-55 °C to +135 °C
<b>Recov. Ø d max.</b>	4.0 mm
<b>Shrink Ratio</b>	3:1
<b>Specifications</b>	CSA   C22.2 no. 198.1-06
<b>Supplied Ø D min.</b>	12.0 mm
<b>Tensile Strength</b>	14 MPa
<b>Wall (WT)</b>	0.85 mm

RoHS

