

## Technical data sheet

Article number:  
301-10001

**SA47 7.5/1.65**

<b>Product Group</b>	Heat shrinkable tubing 4:1 - 1.2 m lengths
<b>Product Family</b>	SA47 - standard wall adhesive lined
<b>Material</b>	Polyolefin, cross-linked (PO-X)
<b>Colour</b>	Transparent (CL), Black (BK)
<b>Adhesive</b>	Hot melt adhesive
<b>Behaviour at Heat Shock</b>	not cracking
<b>Dielectric Strength [Test method]</b>	20 kV/mm [ASTM D149]
<b>Elongation at break [Test method]</b>	450% [ASTM D2671]
<b>Heat Shock Test</b>	4h/225°C
<b>Longitudinal Change After Shrinkage</b>	-10% max.
<b>Min. Shrink Temperature - °C</b>	+130 °C
<b>Operating Temperature</b>	-40 °C to +125 °C
<b>Package Content packed in</b>	pcs.
<b>Pack Cont.</b>	1.2 m
<b>Recov. Ø d max.</b>	1.65 mm
<b>Shrink Ratio</b>	4:1
<b>Supplied Ø D min.</b>	7.5 mm
<b>Tensile Strength [Test method]</b>	14 MPa [ASTM D2671]
<b>Wall (WT)</b>	1.4 mm
<b>Water Absorption</b>	0.5 %

HF ✓

RoHS ✓