

## Technical data sheet

**Article number:**  
**301-10022**

**SA47-LA-11.0/2.4**

<b>Product Group</b>	4:1 Heat shrink tubing - 1.2m lengths
<b>Product Family</b>	SA47-LA - standard wall adhesive lined for perfect corrosion protection
<b>Material</b>	Polyolefin, cross-linked (PO-X)
<b>Colour</b>	Transparent (CL), Black (BK)
<b>Adhesive</b>	EVA hot melt adhesive
<b>Behaviour at Heat Shock</b>	not cracking
<b>Dielectric Strength</b>	20 kV/mm
<b>Elongation at break</b>	450%
<b>Heat Shock Test</b>	4h/225°C
<b>Longitudinal Change After Shrinkage</b>	-10% max.
<b>Min. Shrink Temperature - °C</b>	+130 °C
<b>Operating Temperature</b>	-40 °C to +125 °C
<b>Pack Cont.</b>	1.2 m
<b>Recov. Ø d max.</b>	2.4 mm
<b>Shrink Ratio</b>	4:1
<b>Supplied Ø D min.</b>	11.0 mm
<b>Tensile Strength</b>	14 MPa
<b>Wall (WT)</b>	1.8 mm
<b>Water Absorption</b>	0.5 %

