

## Technical data sheet

Article number:  
321-40008

HR47-95/29



<b>Product Group</b>	Heat shrinkable tubing up to 4:1, self-extinguishing, halogen-free – 1 m lengths
<b>Product Family</b>	HR47 – thick-walled
<b>Material</b>	Polyolefin, cross-linked (PO-X)
<b>Colour</b>	Black (BK)
<b>Dielectric Strength</b>	15 kV/mm
<b>Elongation at break</b>	350%
<b>Elongation At Heat Aging</b>	300 %
<b>Heat Aging Test</b>	168h/150°C
<b>Longitudinal Change After Shrinkage</b>	10% max.
<b>Min. Shrink Temperature - °C</b>	+120 °C
<b>Minimum Tensile Strength At Heat Aging</b>	12 MPa
<b>Operating Temperature</b>	-55 °C to +110 °C
<b>Recov. Ø d max.</b>	29.00 mm
<b>Shrink Ratio</b>	up to 4:1
<b>Specifications</b>	EN [45545-2]]
<b>Supplied Ø D min.</b>	95.00 mm
<b>Tensile Strength</b>	12 MPa
<b>Wall (WT)</b>	4.20 mm
<b>Water Absorption</b>	0.2 %

HF ✓ RoHS ✓

EN 45545-2