

## Technical data sheet

Article number:  
323-25204

MM30 45/12 1m length



|                                                   |                                       |
|---------------------------------------------------|---------------------------------------|
| <b>Material</b>                                   | Polyolefin, cross-linked (PO-X)       |
| <b>Colour</b>                                     | Black (BK)                            |
| <b>Adhesive</b>                                   | Mastic glue                           |
| <b>Behaviour at Heat Shock</b>                    | not cracking, not fluid, not dripping |
| <b>Behaviour at Low Temperature [Test method]</b> | not cracking [ASTM D2671]             |
| <b>Dielectric Strength [Test method]</b>          | 15 kV/mm [IEC 60243]                  |
| <b>Elongation at break [Test method]</b>          | 200 [ASTM D2671]                      |
| <b>Elongation At Heat Aging</b>                   | 100 %                                 |
| <b>Heat Aging Test [Test method]</b>              | 168h/150°C [ASTM D2671]               |
| <b>Heat Shock Test</b>                            | 4h/225°C                              |
| <b>Longitudinal Change After Shrinkage</b>        | -10% max.                             |
| <b>Min. Shrink Temperature - °C</b>               | +120 °C                               |
| <b>Minimum Tensile Strength At Heat Aging</b>     | 8 MPa                                 |
| <b>Operating Temperature</b>                      | -40 °C to +120 °C                     |
| <b>Package Content packed in</b>                  | pcs.                                  |
| <b>Recov. Ø d max.</b>                            | 12.0 mm                               |
| <b>Shrink Ratio</b>                               | up to 5:1                             |
| <b>Supplied Ø D min.</b>                          | 45.0 mm                               |
| <b>Tensile Strength [Test method]</b>             | 12 MPa [ASTM D2671]                   |
| <b>Wall (WT)</b>                                  | 2.50 mm                               |

RoHS

