

## Technische datasheet

Artikel Nummer  
333-32400

TF31-24/8



|                                     |                                         |
|-------------------------------------|-----------------------------------------|
| Productgroep                        | Krimpkous 3:1 flexibel, diverse kleuren |
| Productfamilie                      | TF31                                    |
| Materiaal                           | Polyolefine vernet (PO-X)               |
| Kleur                               | zwart (BK)                              |
| Brandbaarheid                       | UL224 VW1                               |
| Breekspanning [Testmethode]         | 4% [ASTM D638]                          |
| Certificering                       | ANSI/UL 224, CSA-C22.2 No.198.1-99      |
| Diëlektrische sterkte               | 30 kV/mm                                |
| Gebruikstemperatuur - °C            | -55 °C tot +135 °C                      |
| Hitteschoktest                      | 4h/250°C                                |
| Hitteveroudering rek (%)            | 400 %                                   |
| Hitteverouderingstest [Testmethode] | 168h/158°C [SAE-AMS-DTL-23053]          |
| Hoeveelheid per                     | rol                                     |
| Inhoud                              | 30 m                                    |
| Krimpverhouding                     | 3:1                                     |
| Lage temperatuur testmethode        | UL 224                                  |
| Lengtekrimp                         | +5 % / -15 %                            |
| Maat bij uitlevering Ø D            | 24,0 mm                                 |
| Minimale krimptemperatuur - °C      | +90 °C                                  |
| Na vrije krimp Ø d                  | 8,0 mm                                  |
| Treksterkte [Testmethode]           | 12 MPa [ASTM D638]                      |
| UL-File nummer                      | E143529                                 |
| Wanddikte (WT)                      | 1,20 mm                                 |

