

## Technical data sheet

Article number:  
342-23810

PST-H-38.0-19.0



|                                        |                                                        |
|----------------------------------------|--------------------------------------------------------|
| Product Group                          | Heat Shrinkable Tubing 2:1 - Elastomer                 |
| Product Family                         | PST-H                                                  |
| Material                               | Elastomer, cross-linked (POA)                          |
| Colour                                 | Black (BK)                                             |
| Behaviour At Low Temperature           | not cracking                                           |
| Dielectric Strength [Test method]      | 20 kV/mm [IEC 684 P2]                                  |
| Elongation At Heat Aging               | 350 %                                                  |
| Heat Shock Elongation                  | 350 %                                                  |
| Heat Shock Tensile Strength            | 14 MPa                                                 |
| Heat Shock Test                        | 4h/208°C                                               |
| Longitudinal Change After Shrinkage    | -10% max.                                              |
| Min. Shrink Temperature - °C           | +135 °C                                                |
| Minimum Tensile Strength At Heat Aging | 14 MPa                                                 |
| Operating Temperature                  | -75 °C to +150 °C                                      |
| Package Content packed in              | metre                                                  |
| Pack Cont.                             | 30 m                                                   |
| Recov. Ø d max.                        | 19.0 mm                                                |
| Shrink Ratio                           | 2:1                                                    |
| Specifications                         | DEF STAN 59-97/3, LEA, NF F 00-608, VG 95343-5:2006-06 |
| Supplied Ø D min.                      | 38.0 mm                                                |
| Wall (WT)                              | 2.40 mm                                                |

RoHS

