

## Technical data sheet

Article number:  
344-10201

**LVR-1.6/0.8**



|                                            |                                                 |
|--------------------------------------------|-------------------------------------------------|
| <b>Product Group</b>                       | Heat shrinkable tubing 2:1 - PVC                |
| <b>Product Family</b>                      | LVR                                             |
| <b>Material</b>                            | Flexible Polyvinyl Chloride, cadmium free (PVC) |
| <b>Colour</b>                              | Black (BK)                                      |
| <b>Dielectric Strength</b>                 | 22 kV/mm                                        |
| <b>Flammability</b>                        | ASTM D2671                                      |
| <b>Longitudinal Change After Shrinkage</b> | +/-10% max                                      |
| <b>Min. Shrink Temperature - °C</b>        | +80 °C                                          |
| <b>Operating Temperature</b>               | -30 °C to +105 °C                               |
| <b>Package Content packed in</b>           | reel                                            |
| <b>Pack Cont.</b>                          | 500 m                                           |
| <b>Recov. Ø d max.</b>                     | 0.8 mm                                          |
| <b>Shrink Ratio</b>                        | 2:1                                             |
| <b>Supplied Ø D min.</b>                   | 1.6 mm                                          |
| <b>Wall (WT)</b>                           | 0.40 mm                                         |

**RoHS** ✓