

## Technical data sheet

Article number:  
533-65033

TLFD254DS-2X25YE



|                                     |                                                                                                                                                                 |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Group</b>                | Shrinkable markers "Ladder Style", thermal transfer                                                                                                             |
| <b>Product Family</b>               | TLFD DS – 2:1 Rail Limited Fire Hazard, fluid resistant "Ladder Style"                                                                                          |
| <b>Material</b>                     | Polyolefin, cross-linked (PO-X)                                                                                                                                 |
| <b>Colour</b>                       | Yellow (YE)                                                                                                                                                     |
| <b>Dielectric Strength</b>          | 19.7 kV/mm                                                                                                                                                      |
| <b>Min. Shrink Temperature - °C</b> | +120 °C                                                                                                                                                         |
| <b>Operating Temperature</b>        | -55 °C to +125 °C                                                                                                                                               |
| <b>Package Content packed in</b>    | carton                                                                                                                                                          |
| <b>Pack Cont.</b>                   | 2000 pcs.                                                                                                                                                       |
| <b>Print Method</b>                 | thermal transfer print                                                                                                                                          |
| <b>Recommended Ribbon Type</b>      | TTDTHOUT                                                                                                                                                        |
| <b>Recov. Ø d max.</b>              | 12.7 mm                                                                                                                                                         |
| <b>Shelf Life</b>                   | 24 months                                                                                                                                                       |
| <b>Shrink Ratio</b>                 | 2:1                                                                                                                                                             |
| <b>Specifications</b>               | DIN EN 50343:2014 Appendix H, EN 45545-2                                                                                                                        |
| <b>Storage conditions</b>           | 50% relative humidity., The storage in the original packaging is recommended., Please avoid warehousing under impacts such as high humidity, heat and coldness. |
| <b>Supplied Ø D min.</b>            | 26.25 mm                                                                                                                                                        |
| <b>Thermal Transfer Printer</b>     | TT431, TT4030DS, TT4030                                                                                                                                         |
| <b>Wall (WT)</b>                    | 0.63 mm                                                                                                                                                         |

HF ✓

LFH ✓

RoHS ✓

EN 45545-2

EN 50343