

## Technical data sheet

Article number:  
553-50089

**HST6-2WH-3S**



|                                     |                                                           |
|-------------------------------------|-----------------------------------------------------------|
| <b>Product Group</b>                | Shrinkable Wire Markers: "Ladder Style", thermal transfer |
| <b>Product Family</b>               | ShrinkTrak                                                |
| <b>Material</b>                     | Polyolefin, cross-linked (PO-X)                           |
| <b>Colour</b>                       | White (WH)                                                |
| <b>Dielectric Strength</b>          | 19.7 kV/mm                                                |
| <b>Flammability</b>                 | UL 224 VW-1                                               |
| <b>Min. Shrink Temperature - °C</b> | +90 °C                                                    |
| <b>Operating Temperature</b>        | -55 °C to +135 °C                                         |
| <b>Package Content packed in</b>    | pack                                                      |
| <b>Pack Cont.</b>                   | 4000 pcs.                                                 |
| <b>Print Method</b>                 | thermal transfer print                                    |
| <b>Recommended Ribbon Type</b>      | TTDTHOUT, TTDTHOUTSM, TT822OUT, TT822OUTSM                |
| <b>Recov. Ø d max.</b>              | 2.2 mm                                                    |
| <b>Shrink Ratio</b>                 | 3:1                                                       |
| <b>Specifications</b>               | CEN                                                       |
| <b>Supplied Ø D min.</b>            | 6.0 mm                                                    |
| <b>Thermal Transfer Printer</b>     | TT431, TT4030                                             |
| <b>Wall (WT)</b>                    | 0.71 mm                                                   |

