


Technische datasheet

Artikel Nummer
553-60002

TLFX48DS-1x50WH



Productgroep	Bedrukbare krimpkous, ladderformaat, thermotransferprinter
Productfamilie	TLFX DS - 2:1 rail Limited Fire Hazard in ladderformaat
Materiaal	Polyolefine vernet (PO-X)
Kleur	wit (WH)
Aanbevolen tonerband	TTDTHOUT
Breekspanning [Testmethode]	200 % [ASTM D2671]
Certificering	ASTM 1354, ASTM E 162, ASTM E 662, EN 45545-2, NFPA 130 compliant
Diëlektrische sterkte [Testmethode]	20 kV/mm [ASTM D2671]
Gebruikstemperatuur - °C	-55 °C tot +105 °C
Hitteschoktest	4h/175°
Hitteverouderingstest [Testmethode]	168h/150°C [ASTM D638]
Hoeveelheid per	verpakking
Houdbaarheid	24 maanden
Inhoud	5000 st.
Krimpverhouding	2:1
Lengtekrimp	-5 % max. [UL 224]
Maat bij uitlevering Ø D	4,8 mm
Minimale krimptemperatuur - °C	+100 °C
Na vrije krimp Ø d	2,4 mm
Printmethode	thermotransfer
Test bij lage temperatuur [Testmethode]	4h/-40°C [ASTM D2671]
Thermotransfer printer	TT431, TT4030DS, TT4030
Toxiciteitsindex [Testmethode]	0,03 (CITg) [EN 17084]
Treksterkte [Testmethode]	11 MPa [ASTM D2671]
Volumeweerstand [Testmethode]	10 ¹⁴ Ω cm [ASTM D257]
Wanddikte (WT)	0,635 mm
Waterabsorptie	0,15 %
Zuurstof-index	34,9 % [ISO 4589]



EN 45545-2

ASTM

NFPA 130

