

Technische datasheet

Artikel Nummer
554-50900

TLFX508WH



Productgroep	Bedrukbare krimpkous, rolmateriaal, thermotransferprinter
Productfamilie	TLFX - 2:1 rail Limited Fire Hazard
Materiaal	Polyolefine vernet (PO-X)
Kleur	wit (WH)
Aanbevolen tonerband	TTDTHOUT
Breekspanning [Testmethode]	4.5 [ASTM D2671]
Certificering	EN 45545-2
Gebruikstemperatuur - °C	-55 °C tot +125 °C
Hitteschoktest	4h/150°C
Hitteverouderingstest [Testmethode]	168h/150°C [ASTM D638]
Hoeveelheid per	karton
Inhoud	10 m
Krimpverhouding	2:1
Lengtekrimp	-5 % max. [UL 224]
Maat bij uitlevering Ø D	50,8 mm
Minimale krimptemperatuur - °C	+70 °C
Na vrije krimp Ø d	25,4 mm
Printmethode	thermotransfer print
Test bij lage temperatuur [Testmethode]	1h/-30°C [ASTM D2671]
Thermotransfer printer	TT431, TT4030DS, TT4030
Toxiciteitsindex [Testmethode]	0,02 (CITg) [ISO 5659-2]
Treksterkte [Testmethode]	12 MPa [ASTM D2671]
Volumeweerstand [Testmethode]	10 ¹⁴ Ω cm [ASTM D257]
Wanddikte (WT)	0,73 mm
Zuurstof-index	33,4 % [ISO 4589]

HF ✓ LFH ✓ RoHS ✓

EN 45545-2