


Technical data sheet

Article number:
556-00811

RFID HARDTAG SOLID 105x35



| | |
|----------------------------------|---|
| Product Group | Hard tags with RFID transponder |
| Product Family | ToughLine – Ultra high frequency (UHF), weld-on, blank |
| Material | Acrylonitrile Butadiene Styrene alloyed with Polycarbonate (PC/ABS), Stainless Steel (SS) |
| Colour | Grey (GY) |
| Data Retention | 50 years |
| Fixation Method | weld-on |
| Frequency | 865-956 MHz (UHF) |
| Height (H) | 15.00 mm |
| Length (L) | 105.00 mm |
| Memory | User memory: 512 bits, EPC: 128 bits, TID: 96 bits |
| Operating Temperature | -40 °C to +80 °C |
| Package Content packed in | bag |
| Pack Cont. | 240 pcs. |
| Radio protocol | ISO 18000-6C, EPC Gen2 |
| Resistance to | Water: 100h (at room temperature), Salt mist: 100h (at room temperature), Petroleum: 100h (at room temperature), Mineral and vegetable oils: 100h (at room temperature) |
| Specifications | IEC 62262: IK09, IEC 68-2-29, IEC 68-2-6 |
| Storage Temperature | -40 °C to +80 °C |
| Type of RFID chip | Impinj Monza 4QT |
| Width (W) | 35.00 mm |

