


## Technical data sheet

Article number:  
556-80530

**TAGPU20X51-4**



|                                          |                                                                        |
|------------------------------------------|------------------------------------------------------------------------|
| <b>Product Group</b>                     | Identification tags for cable bundle, "Ladder Style", thermal transfer |
| <b>Product Family</b>                    | TAGPU – UV-stabilised Tiptags                                          |
| <b>Material</b>                          | Polyurethane (PUR)                                                     |
| <b>Colour</b>                            | White (WH)                                                             |
| <b>Elongation at break [Test method]</b> | 400% [DIN 53504]                                                       |
| <b>Flammability</b>                      | UL 94 V0 (3 mm)                                                        |
| <b>H printable</b>                       | 20.4 mm                                                                |
| <b>Length (L)</b>                        | 51.5 mm                                                                |
| <b>Operating Temperature</b>             | -25 °C to +105 °C                                                      |
| <b>Oxygen index [Test method]</b>        | 24 % [ISO 4589]                                                        |
| <b>Package Content packed in</b>         | box                                                                    |
| <b>Pack Cont.</b>                        | 1000 pcs.                                                              |
| <b>Print Method</b>                      | thermal transfer print                                                 |
| <b>Recommended Ribbon Type</b>           | TT287, TTRC+                                                           |
| <b>Shelf Life</b>                        | 5 years                                                                |
| <b>Specifications</b>                    | MIL-STD-202G Method 215K, SAE - AS81531                                |
| <b>Strap Width max. (G)</b>              | 4.6 mm                                                                 |
| <b>Tensile Strength [Test method]</b>    | 30 MPa [DIN 53504]                                                     |
| <b>Thermal Transfer Printer</b>          | TT431, TT4030                                                          |
| <b>UV-Stabilised</b>                     | Yes                                                                    |
| <b>Width (W)</b>                         | 20.4 mm                                                                |
| <b>Width of Liner (WL)</b>               | 90.0 mm                                                                |
| <b>Width printable</b>                   | 32.7 mm                                                                |

