


Technical data sheet

Article number:
556-83029

TAGLF12X60-4



Product Group	Identification tags for cable bundle "Ladder Style", thermal transfer
Product Family	TAGLF – Rail - Limited Fire Hazard Tiptags
Material	Polyolefin, cross-linked (PO-X)
Colour	Yellow (YE)
Dielectric Strength [Test method]	20.0 kV/mm [ASTM D149]
Elongation at break [Test method]	200 % [ASTM D638]
Flammability	ASTM D635
Heat Aging Test	168h/150°C
Heat Shock Test	4h/150°C
H printable	12.0 mm
Length (L)	60.0 mm
Operating Temperature	-40 °C to +105 °C
Oxygen index [Test method]	34.9 % [ISO 4589]
Package Content packed in	box
Pack Cont.	1000 pcs.
Print Method	thermal transfer print
Recommended Ribbon Type	TTDTHOUT
Shelf Life	5 years
Smoke density [Test method]	44 Ds (max) [ISO 5659-2]
Specifications	EN 45545-2, MIL-STD-202G Method 215K, SAE - AS81531
Strap Width max. (G)	4.6 mm
Test Method Tensile Strength	ASTM D638
Thermal Transfer Printer	TT431, TT4030
Toxicity index [Test method]	0.03 CITg [EN 17084]
Width (W)	11.6 mm
Width of Liner (WL)	90.0 mm
Width printable	40.0 mm

HF✓ LFH✓ RoHS✓

EN 45545-2 MIL SAE®