


## Technical data sheet

Article number:  
596-01903

**TAG32-230TD1**



<b>Product Group</b>	Self-laminating labels, thermal transfer
<b>Product Family</b>	Helatag 1232
<b>Material</b>	Type 1232, Polyester, white transparent, self-laminating (1232)
<b>Colour</b>	White (WH), Transparent (CL)
<b>Adhesive</b>	Acrylic
<b>Application Method</b>	The functionality and durability of the labels can be negatively affected if improperly processed or applied. All surfaces to be bonded must be clean, dry as well as free from dust and grease. Avoid touching the adhesive surface of the label as this could impair the application performance.
<b>Bundle Ø max.</b>	50.8 mm
<b>Bundle Ø min.</b>	30.24 mm
<b>Chem. Material Properties</b>	Resistant to water, alcohol, most oils, greases, fuel, aliphatic solvents, weak acids, salts and alkalis.
<b>Curing Temperature</b>	from +2 °C
<b>Height (H)</b>	60.00 mm
<b>Height (H2)</b>	228.6 mm
<b>Labels per Row</b>	1 pc.
<b>Material Durability</b>	10 years external weathering (central European climate)
<b>Mech. material properties</b>	Due to its flexibility particularly suitable for identification of cables.
<b>Operating Temperature</b>	-40 °C to +150 °C
<b>Package Content packed in</b>	pack
<b>Pack Cont.</b>	400 pcs.
<b>Print Method</b>	thermal transfer print
<b>Recommended Ribbon Type</b>	TT822OUT
<b>Resistance to</b>	Brake cleaner: 720h (at room temperature), Alcohol 94%: 720h (at room temperature), Hydraulic oil: 720h (at room temperature)
<b>Thermal Transfer Printer</b>	TT431, TT4030
<b>Thickness of Foil</b>	50 µm

<b>UV-Stabilised</b>	Yes
<b>Width of Liner (WL)</b>	38.00 mm
<b>Width (W)</b>	31.75 mm

