

## Technical data sheet

Article number:  
596-12086

**TAG66TD1**



<b>Product Group</b>	Tamper-evident security labelling, thermal transfer
<b>Product Family</b>	Helatag 1208, fragmenting
<b>Material</b>	Type 1208, Acetate foil, white, tamper-proof (1208)
<b>Colour</b>	White (WH)
<b>Adhesive</b>	Acrylic
<b>Application Method</b>	The functionality and durability of the labels can be negatively affected if improperly processed or applied. All surfaces to be bonded must be clean, dry as well as free from dust and grease. Avoid touching the adhesive surface of the label as this could impair the application performance.
<b>Curing Temperature</b>	from +4 °C
<b>Flammability</b>	UL 94 V1
<b>Height (H)</b>	36.50 mm
<b>Labels per Row</b>	1 pc.
<b>Operating Temperature</b>	-40 °C to +150 °C
<b>Print Method (Alternative)</b>	laser beam print
<b>Recommended Ribbon Type</b>	TT822OUT
<b>Storage conditions</b>	50% relative humidity., The storage in the original packaging is recommended., Please avoid warehousing under impacts such as high humidity, heat and coldness.
<b>Storage Temperature</b>	+21 °C
<b>Thickness of Adhesive (TA) nom.</b>	0.020 mm
<b>Thickness of Foil</b>	56 µm
<b>Width of Liner (WL)</b>	56.80 mm
<b>Width (W)</b>	50.80 mm

