

## Technical data sheet

Article number:  
596-53932

**TAG76-32TT**



<b>Product Group</b>	Non-adhesive cable marking labels, thermal transfer
<b>Product Family</b>	Helatag 932
<b>Material</b>	Type 932, Polyolefin, white (932)
<b>Colour</b>	White (WH)
<b>Chem. Material Properties</b>	Resistant against alcohol, water, oils, acetone, tulone and petrols.
<b>Curing Temperature</b>	from 0 °C
<b>Height (H)</b>	31.75 mm
<b>Labels per Row</b>	1
<b>Material Durability</b>	At vertical exposure to weathers (central European climate) 2 years.
<b>Mech. material properties</b>	Flexible material ideally suited for cable marking
<b>Operating Temperature</b>	-40 °C to +90 °C
<b>Package Content packed in</b>	reel
<b>Pack Cont.</b>	1000 pcs.
<b>Print Method</b>	thermal transfer print
<b>Print Method (Alternative)</b>	laser beam print
<b>Recommended Ribbon Type</b>	TT822OUT
<b>Storage conditions</b>	50% relative humidity., The storage in the original packaging is recommended.
<b>Storage Temperature</b>	+21 °C
<b>Thickness of Foil [Test method]</b>	280 µm [ASTM D3652-83]
<b>Width (W)</b>	76.20 mm

