


## Technical data sheet

Article number:  
596-91209

TAG9TD3



<b>Product Group</b>	Self-laminating labels, thermal transfer
<b>Product Family</b>	Helatag 1209
<b>Material</b>	Type 1209, Vinyl (1209)
<b>Colour</b>	White (WH), Transparent (CL)
<b>Adhesive</b>	Acrylic
<b>Application Method</b>	The functionality and durability of the labels can be negatively affected if improperly processed or applied. All surfaces to be bonded must be clean, dry as well as free from dust and grease. Avoid touching the adhesive surface of the label as this could impair the application performance.
<b>Bundle Diameter max (metric)</b>	12.1 mm
<b>Bundle Ø min.</b>	5.5 mm
<b>Chem. Material Properties</b>	Resistant to water, alcohol, most oils, greases, fuel, aliphatic solvents, weak acids, salts and alkalis.
<b>Curing Temperature</b>	from 0 °C
<b>Height (H)</b>	19.05 mm
<b>Height (H2)</b>	57.10 mm
<b>Labels per Row</b>	3 pcs.
<b>Operating Temperature</b>	-20 °C to +80 °C
<b>Package Content packed in</b>	reel
<b>Pack Cont.</b>	2500 pcs.
<b>Print Method</b>	thermal transfer print
<b>Print Method (Alternative)</b>	laser beam print
<b>Recommended Ribbon Type</b>	TT932DOUT
<b>Thickness of Foil</b>	90 µm
<b>Width of Liner (WL)</b>	82.0 mm
<b>Width (W)</b>	25.40 mm

